

PierPump S160

When considering the technical and ecological aspects of waste water & bilge water collection from boats and yachts, the PierPump S160 is the answer for well proven and reliable waste water disposal services.

The service station, which is typically installed on the pier or landing stage, is equipped with a heavy duty, high performance VOGELSANG rotary lobe pump. The powerful positive displacement pump provides vacuum to collect the bilge- or waste water from the boat tank and simultaneously discharges it into the sewer or other waste water collection systems.

The PierPump S160 provides high discharge rates but also a small footprint which allows installing the system where space is restricted.

Features:

- High waste water extraction & discharges rates
- Totally closed system, no offensive smells
- Self-priming & robust Vogelsang rotary lobe pump package
- Insensitive to dry-running
- Small footprint & compact size
- Weather proof enclosure made of Stainless Steel
- Simple & easy handling
- Maintenance friendly pump design

Options:

- Coin-operation device
- Dry-running control
- Timer relay control
- Operating hour metre
- Electrical heater for frost protection
- Pump wet-end housing, inlet & discharge piping available in Stainless Steel



PierPump S160 for harbours & marina areas

Specification PierPump S160

VOGELSANG rotary lobe pump type:	V100-45Q HD
Capacity up to:	180 L/Min
Suction lift up to:	8 mWC
Differential pressure up to:	2 bar
Power:	2,2 kW
Voltage:	3Ph x 230/400Volt 50Hz
Inlet & Discharge piping:	Steel galv.
Enclosure & Hose Rack:	Stainless Steel 316Ti
Suction hose dia.:	DN40
Hose length:	15 m
Hose accessories:	2"-ball valve with KAMLOK adaptor
Dimensions LxWxH approx.:	960x580x1050 mm
Weight approx.:	295 kg

